



### Trail Uses



No Dogs



Equestrian



Bicycling



Hiking



No Motorized Vehicles

### Hazards and Obstructions



Steps  
one step  
2 in

# Wildcat Creek and Boardwalk Loop

Wildcat Canyon

## Trail Length 0.6 mi (1.0 km) trail

If you have little ones then this is the trail for you. Starting at the Tilden Nature Area, you will enjoy a quiet, easy stroll along eucalyptus trees and ground squirrels. Once you reach Jewel Lake, take a sharp right and head back along Jewel Lake, where turtles lounge and birds nap.

Cumulative Gain 13 ft (4 m)  
Elevation Change Loss 38 ft (11 m)



### Typical Grade is 15%

1% of the trail is between 8% and 34%  
20 ft (6 m) is between 12% and 34%  
8% grade is a standard ramp.



### Typical Cross Slope is 2.1%

6% of the trail is between 5% and 17%  
67 ft (20 m) is between 10% and 17%



### Typical Tread Width is 100 in (254 cm)

Tread Width ranges from 35 in (89 cm) to 216 in (549 cm)  
Minimum Clearance 39 in (99 cm)



### Trail Surface is Aggregate/Gravel

100% of the trail is Firm or better  
0 ft (0 m) of the trail is Soft or worse

### Trailhead Location

This trail begins at the end of the parking lot at the Tilden Nature Area.



### Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 2.0 in (5.0 cm) or outside the tread area 120 in (3 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 20 in (50 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

# Wildcat Creek and Boardwalk Loop

---

Length 0.6 mi (1.0 km)

trail

---



No Dogs



Equestrian



Bicycling

---



Typical Grade 1.5%

---

1% of the trail is  
8% to 34%

20 ft (6 m) is 12% to 34%  
8% grade is a standard ramp.

---



Typical Cross Slope 2.1%

---

6% of the trail is  
5% to 17%

67 ft (20 m) is 10% to 17%

---



Typical Tread Width  
100 in (254 cm)

---

Minimum 35 in (89 cm)

Maximum 216 in (549 cm)

Minimum Clearance 39 in (99 cm)

---



Aggregate/Gravel

---

100% is Firm or better

0 ft (0 m) is Softer or worse

---



Steps

one step  
2 in

---



Trail Access  
Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 05

# Wildcat Creek and Boardwalk Loop

Wildcat Canyon

Trail Access Information Summary

Trail Length 0.6 mi (1.0 km)

trail

First Segment Assessed

page 1

Aug 22, 05

Last Segment Assessed

Aug 22, 05

## Cumulative Elevation Change

Gain 13 ft (4 m)

Loss 38 ft (11 m)

---

## Typical Grade is 1.5%

1% of the trail is between 8% and 34%

20 ft (6 m) is between 12% and 34%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

---

## Typical Cross Slope is 2.1%

6% of the trail is between 5% and 17%

67 ft (20 m) is between 10% and 17%

Locations and lengths can be found on the Maximum Cross Slope Table Reports

---

## Typical Tread Width is 100 in (254 cm)

Tread Width ranges from 35 in (89 cm) to 216 in (549 cm)

Minimum Clearance Width is 39 in (99 cm)

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

---

## Trail Surface is Aggregate/Gravel

100% of the trail is Firm or better

0 ft (0 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

---

## Obstructions

Steps one step

2 in

---

## Trail Uses

No Dogs

Equestrian

Bicycling

---

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 2.0 in (5.0 cm) or outside of the tread area a 120 in (3 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 2.0 in (5.0 cm) high.