



Trail Uses



Dogs



Bicycling



Equestrian



Hiking



No Motorized Vehicles

Hazards and Obstructions



Vertical
60 in.



Ruts
3 in.



Noxious
Plants
12 in.

Meadows Canyon

Tilden Regional Park

Trail Length 1.4 mi (2.3 km)

Network trail

This trail is a fire road that connects with the Curran trail and is used by hikers, runners, and dog walkers. It offers scenic views of the valley and of the bay. The trail has moderate grades and may be a tough hike for some.

Cumulative Gain 381 ft (116 m)
Elevation Change Loss 13 ft (4 m)



Typical Grade is 52%

17% of the trail is between 8% and 23%
417 ft (127 m) is between 12% and 23%
8% grade is a standard ramp.



Typical Cross Slope is 9.9%

18% of the trail is between 16% and 30%
263 ft (80 m) is between 20% and 30%



Typical Tread Width is 114 in (290 cm)

Tread Width ranges from 12 in (30 cm) to 183 in (465 cm)
Minimum Clearance 40 in (102 cm)



Trail Surface is Soil

99% of the trail is Firm or better
59 ft (18 m) of the trail is Soft or worse

Trailhead Location

Trail starts at the beginning of Lone Oak Road. Take Wildcat Canyon Rd. to Central Park Dr., and then make a right at Lone Oak Rd.



Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 2.0 in (5.0 cm) or outside the tread area will be by 96 in (24 m) high were not measured. Minimum clearance boundaries were at least 20 in (50 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

Meadows Canyon

Length 1.4 mi (2.3 km)

Network trail



Dogs



Bicycling



Equestrian



Typical Grade 5.2%

17% of the trail is

8% to 23%

417 ft (127 m) is 12% to 23%
8% grade is a standard ramp.



Typical Cross Slope 9.9%

18% of the trail is

16% to 30%

263 ft (80 m) is 20% to 30%



Typical Tread Width

114 in (290 cm)

Minimum 12 in (30 cm)

Maximum 183 in (465 cm)

Minimum Clearance 40 in (102 cm)



Soil

99% is Firm or better

59 ft (18 m) is Soft or worse



Vertical 60 in.



Ruts 3 in.



Noxious Plants 12 in.



Trail Access
Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 25, 05

Meadows Canyon
Tilden Regional Park
Trail Access Information Summary
Trail Length 1.4 mi (2.3 km)
Network trail

First Segment Assessed Jun 15, 05
Last Segment Assessed Jun 15, 05

page 1

Cumulative Elevation Change

Gain 381 ft (116 m)

Loss 13 ft (4 m)

Typical Grade is 5.2%

17% of the trail is between 8% and 23%

417 ft (127 m) is between 12% and 23%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

Typical Cross Slope is 9.9%

18% of the trail is between 16% and 30%

263 ft (80 m) is between 20% and 30%

Locations and lengths can be found on the Maximum Cross Slope Table Reports

Typical Tread Width is 114 in (290 cm)

Tread Width ranges from 12 in (30 cm) to 183 in (465 cm)

Minimum Clearance Width is 40 in (102 cm)

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

Trail Surface is Soil

99% of the trail is Firm or better

59 ft (18 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

Obstructions

Vertical 60 in.

Ruts 3 in.

Noxious Plants 12 in.

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

Trail Uses

Dogs

Bicycling

Equestrian

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 2.0 in (5.0 cm) or outside of the tread area are wide by 96 in (24 m) high were not measured. Minimum clearance boundaries were at least 20 in (50 cm) high.